




CATIA V5



Revision Level			Revision Record	Changed	Date	Approved	Date
Drawing	State	Part					
01.1	Design Release	-	SEE ECN# 014954	NHK	02/28/19	EJF	02/28/19



ISOMETRIC VIEW
SCALE 1:2

REFERENCE:

PERFORMANCE REQUIREMENTS AT DRY AS MOLDED:

1. STUD MOUNT PUSH ON FORCE: 45 NEWTONS (10 LBS) MAX ON EACH APPLICABLE STUD SIZE
2. STUD MOUNT PULL OFF FORCE: 223 NEWTONS (50 LBS) MIN ON EACH APPLICABLE STUD SIZE
3. APPLICABLE STUD SIZE:
 - A. M5 X 0.8
 - B. M6 X 1
 - C. T5
 - D. T6
4. CABLE TIE MIN LOOP TENSILE STRENGTH: 355 NEWTONS (80 LBS)
5. BUNDLE RANGE: 3.5mm TO 50.0mm
6. MAX ALLOWABLE FLASH TO BE 0.25mm
7. MAX ALLOWABLE MISMATCH TO BE 0.1mm

Material	Units millimeters	The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.	Drawn	NHK	0/2/11/19	Article/Type-No	T80ROSLPSB5-6U	Scale	3:4
			Approved	EJF	02/11/19	Title	M5/M6 LOW PROFILE STUD MOUNT WITH T80 CABLE TIE	Project Number	19-0235
COLOR: SEE CHART			<p>North America Email: corp@htamericas.com Web: www.hellermann.tyton.com</p>			Drawing-No	DEVELOPMENT : Phase	Format	AH
						19-0235-001-CSU			Sheet